

```
<!--
```

This one is written first for non-IE browsers, and addresses IE browsers using PHP. It does NOT require duplicate code.

```
-->
```

```
<object id="wmp_p" data="video/CIMG2770.AVI"
  <?php //test for IE and if true, insert CLASSID for WMP
  $user = ' ' . $_SERVER['HTTP_USER_AGENT'];
  if (strpos($user, 'MSIE')) {
    echo "CLASSID=\"CLSID:6BF52A52-394A-11d3-B153-00C04F79FAA6\" " ;
  }
  ?>
  type="application/x-ms-wmp"
  width="320" height="240"
  style="position:relative; left:50px;top:0;">
  <param name="autostart" value="false" />
  <param name="volume" value="50" />
  <param name="URL" value="video/CIMG2770.AVI" >
  <p class="smallspacing">Error - the plugin has not loaded </p>
</object>
```

```
<!--
```

With ClassID, the player was visible in IE, but not "enabled"

With the Param NAME="URL" line, the player was enabled in IE

However, with ClassID, Firefox no longer saw the player

```
-->
```

```
<br/>
```

```
<br/>
```

```
<!--
```

This one is written first for IE browsers, then addresses non-IE browsers using a "not-IE" (!IE) comment.

It requires duplicate code.

```
-->
```

```
<object id="wmp2" type="application/x-oleobject"
  classid="CLSID:6BF52A52-394A-11d3-B153-00C04F79FAA6"
  width="320" height="240"
  style="position:relative; left:50px;top:0;">
  <param name="url" value="video/CIMG2770.AVI" >
  <param name="autostart" value="false" />
  <param name="volume" value="50" />
  <!--[if !IE]>-->
  <!-- also works if you use application/x-ms-wmp -->
  <object data="video/CIMG2770.AVI" type="application/x-mpplayer2"
    width="320" height="240"
    style="position:relative; left:0px;top:0;">
    <param name="url" value="video/CIMG2770.AVI" >
    <param name="autostart" value="false" />
    <param name="volume" value="50" />
  </object>
  <!--<![endif]>-->
</object>
```